

SPECIALTY PRODUCTS**ASPHALT RELEASE AGENT B44****FEATURES**

- Non Hazardous
- Based on natural oils
- Long lasting
- Release Agent for all Asphalt formulations
- Resists low and high temperatures
- Non-chlorinated, hydrocarbon solvents, no diesel
- Safe to the environment

PROPERTIES

Appearance: Yellow/Tan liquid with a characteristic oil odor

Vapor density: >1

Boiling point: 245 F

Specific gravity: 0.86-0.88 gr/cc

Chemical type: Soy oil

Storage stability: Keep away from open flame and below 120 °F.

Flash point: > 270 F

Flammability: Non Flammable

Solubility in water: Emulsifies

Packaging: 5 gal pails
55 gal drums

- Properties are typical and subject to usual manufacturing tolerances.

ASPHALT RELEASE AGENT B44 is a surface active release agent, based in a selected blend of natural oils. It acts as a powerful lubricant and as a release agent. This product is slow drying, low odor, biodegradable and non toxic. It is excellent at reducing low speed friction and facilitates the slip of all types of asphalt formulations when in contact with metal flat beds and other surfaces. It also has excellent film forming properties and resists high and low temperatures making it useful for all weather applications. Preferably clean the surface to be treated and dry. Apply by spraying 8 to 12 inches from surface and spray a thin film over whole area. Repeated applications will favor faster release. Can dilute with water up to 10 times for repeated use. Do not use near heat, open flame or sparks. Can be cleaned with water, with a pressure washer. Refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron
3911 SW 47th AVE
Davie, Florida 33314
Tel: (954) 584 - 4530
Fax: (954) 584 - 4531
www.chemtron.com

