

## OILS AND LUBRICANTS

# DRY SILICONE SPRAY

**FEATURES**

- Food grade lubricant
- Silicone based lubricant
- Non-oily, fast drying
- Low odor and stainless coating
- Safe on plastics and most surfaces
- Non-chlorinated, Non-Hexane solvents
- Repels water and protects against corrosion and rust

**PROPERTIES**

**Appearance:** Colorless liquid with a characteristic solvent odor

**Boiling point:** 33.7 °F

**Vapor density:** >1

**Specific gravity:** 0.582 gr/cc

**Chemical type:** Silicone oil

**Storage stability:** Keep away from open flame and below 120 °F.

**Vapor pressure:** 60-70 psig

**Flash point:** Level 3 aerosol (-156 °F)

**Flammability:** Flammable spray

**Solubility in water:** Negligible

**Packaging:** 12x11oz Net Wt. Cans/Case

- Properties are typical and subject to usual manufacturing tolerances.

DRY SILICONE SPRAY is a lubricant and release agent that reduces friction and eliminates sticking and binding on metals, plastics, rubber, fabrics, glass and laminated surfaces. This product is fast drying, low odor, non-staining, making it ideal for uses where stains or strong odors are not desired. Treated areas repel moisture and are protected against corrosion and wear. DRY SILICONE SPRAY is formulated with a high molecular weight silicone polymer that makes it heat stable at temperatures between -40°F and +450°F. It can be used in the Food packaging and processing industry with incidental food contact, tables conveyors, heat sealing equipment, slicing equipment. It can also be used on ovens and hoods to prolong time between cleanings. Prevents jamming and production slowdowns on bottling lines. Just spray onto clean dry surface and allow to set. Do not use near heat, open flame or sparks. Refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron  
3911 SW 47th AVE  
Davie, Florida 33314  
Tel: (954) 584 - 4530  
Fax: (954) 584 - 4531  
[www.chemtron.com](http://www.chemtron.com)

