

**Electrical Cleaner****ELECTRONIC CONTACT CLEANER****FEATURES**

- Can be used in not energized electrical motors
- Fast drying
- Ideal for removing dirt and grease from sensitive electronic equipment
- Will not harm plastics, paint or wire insulation

**PROPERTIES**

**Appearance:** Clear with solvent odor.

**Boiling point:** 151 °F

**Specific gravity:** 0.80 + 0.05 gr/cc

**Vapor Density:** Heavier than air

**Solubility in water:** Soluble

**Ingredients:** Heptane, 1,1-Diofluoroethane, Propane.

**Storage stability:** Keep away from direct sun light and open flames, and temperatures below 120°F (49°C)

**pH:** NA

**Flammability:** Flammable

**Packaging:** 12x16oz Net Wt. Cans/Case

- Properties are typical and subject to usual manufacturing tolerances.

ELECTRONIC CONTACT CLEANER is a fast drying, residue free aerosol that removes all types of contamination (grease, oil, dust) from electrical equipment.

Ideal for removing dirt and grease from delicate or sensitive electronic equipment. It will not harm most plastics, paint, or wire insulation like chlorinated substances. Its 3-way action cleans, restores, and protects. Leaves no residue. Effectively cleans and degreases de-energized electric motors, generators, starter motors, relays, circuit breakers, instruments, rheostats, etc. To use this product, disconnect all power and be sure components are completely de-energized. Spray at 6-8 inches — floats dirt and other harmful elements away instantly. Allow to dry before returning power.

Refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron  
3911 SW 47th AVE  
Davie, Florida 33314  
Tel: (954) 584 - 4530  
Fax: (954) 584 - 4531  
[www.chemtron.com](http://www.chemtron.com)

