

## OILS AND LUBRICANTS

**OPEN GEAR & 5th WHEEL LUBRICANT****FEATURES**

- New Special tacking formula prevents sling-off and clings longer in vertical applications
- Forms a flexible film that resists water and prevents corrosion
- Protects and lubricates
- Acts as a grease
- Great penetrating power

**PROPERTIES**

**Appearance:** Tacky, black liquid with characteristic grease odor

**Specific gravity:** 0.855 gr/cc

**Boiling point:** > 400°F

**Chemical type:** Hydrocarbon oils mixture

**Total VOC:** 40%

**Solubility in water:** Not soluble

**Flammability:** Not Flammable

**Packaging:** 6 gal pail


OPEN GEAR & 5TH WHEEL LUBRICANT is a tacky liquid grease that protects all moving metal parts from metal to metal contact. Forms a protective water resistant coating that prevents corrosion in outdoors applications. Provides a flexible coating that lubricates and protects moving metal parts.

It penetrates into wire rope and other roller chain mechanisms. OPEN GEAR & 5TH WHEEL LUBRICANT is formulated with Hydrocarbon special oils and additives, that combine to provide surfaces with superior lubricating properties. It is ideal for outdoors use since it retains its lubricity under acid or salty conditions and will not break down, fly off or wash away with water. It absorbs high shock loads, extreme pressure and prevents chipping and scuffing.

Apply on surface with thick oil dispenser, to impregnate or fill the whole desired part or surface.

Repeat application periodically (once a week is recommended depending machines' operation). Do not apply near open flame or sparks. Caution, flammable liquid. Do not inhale vapors and avoid eyes contact. Refer to SDS for flammability and additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron  
3911 SW 47th AVE  
Davie, Florida 33314  
Tel: (954) 584 - 4530  
Fax: (954) 584 - 4531  
[www.chemtron.com](http://www.chemtron.com)



- Properties are typical and subject to usual manufacturing tolerances.