CT – 475

Ž

Ω

2

Ш

U

Ш

FESS|



SPECIALTY LUBRICANT PENETRATING LUBE

- Penetrates through rust and scale to free frozen parts
- Lubricates parts to reduce friction
- Removes moisture from electrical equipment
- 39,000 Volt Dielectric Strength
- Never Dries Out
- Non-Flammable

PROPERTIES

Appearance: Light brown liquid with solvent odor.
Boiling point: Not Determined
Specific gravity: 1.44 gr/cc
Solubility in water: Insoluble
Flash point: None
Storage stability: Keep away from high temperatures and open flames
pH of liquid: Not Available
Flammability: Non-flammable aerosol
Packaging: 12x12oz Net Wt. Cans/Case

 Properties are typical and subject to usual manufacturing tolerances.

PENETRATING LUBE is а non chlorinated, non-flammable formula that penetrates through rust and scale to loosen parts which have been frozen by corrosion while lubricating them to ensure free and easy movement. PENETRATING LUBE has a dielectric strength of 39,000 Volts. It acts as a demoisturizer, creating a waterproof film that dries out electrical equipment, inhibiting corrosion and preventing electrical discharges. This non-drying film also protects parts against atmospheric conditions and mild chemical corrosion. It meets the military specification MIL-C-23411 for corrosion prevention.

Refer to the label and attached SDS for instructions and precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron 3911 SW 47th AVE Davie, Florida 33314 Tel: (954) 584 - 4530 Fax: (954) 584 - 4531 www.chemtron.com

