

RESISTANT COATING

POLYBAR PRO

FEATURES

- Polymeric-Carbamate blend formula
- Acts as a long lasting surface protective coating
- Does not affect painted surfaces
- Flexible film formation
- Can be added to latex paints
- Fast drying

PROPERTIES

Appearance: Transparent film with no color and no particular odor

Flash point: Non flammable

Specific gravity: 0.98-1.01 gr/cc

Non volatiles: 2-5 %

Solubility in water: Total

Chemical type: Carbamate/ Acrylic blend

Storage stability: Keep away from direct sun light and Acid products.

Boiling point: 100 °C

Packaging: 4 x 1 gallon Case
5 gallon Pails
55 gallon Drum

- Properties are typical and subject to usual manufacturing tolerances.

POLYBAR PRO is a Carbamate based solution, combined with a polymeric compound which forms a coating that resist organic material growth, mold and mildew on hard and soft surfaces, including fabrics, walls and furniture. It can be used in air conditioner systems and ducts. Use POLYBAR PRO undiluted or add 10 oz per gallon of paint. Apply onto clean surface with spray bottle or poly-sprayer or using a brush or roller, and allow to dry. Do not rinse. Avoid contact with eyes. Refer to the SDS for additional precautions.

The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron
3911 SW 47th AVE
Davie, Florida 33314
Tel: (954) 584 - 4530
Fax: (954) 584 - 4531
www.chemtron.com

