

SPECIALTY OILS**SUPER FILM HYDRAULIC OIL ISO-32****FEATURES**

- Contains Oxidation, Rust & Corrosion Inhibitors
- Contains Anti-wear Agents
- Produced with Anti-Foam Agents
- Pour Point Depressants
- Excellent Temperature and Oxidation Stability
- For use in Construction Equipment, Hydraulic Platforms, Cranes, Hatch Covers and more

PROPERTIES

Appearance: Straw (light) colored liquid with mild hydrocarbon odor.

Melting point: -59.8 °F

Specific gravity: 0.84 gr/cc

Non volatiles: Not Determined

Solubility in water: Not Determined

Flash point: (open cup) 442.4 °F

Storage stability: Keep away from oxidizing atmospheric conditions

Flammability: Slightly Flammable

Packaging: 4x1 gallon Case

- Properties are typical and subject to usual manufacturing tolerances.

SUPER FILM HYDRAULIC OIL ISO-32 is the most advanced blend of highly refined paraffin based oils and special additives to assure long oil life under heavy-duty applications. This product is specially formulated with high viscosity index based stocks and anti-wear additives to give excellent temperature and oxidation stability, and to provide maximum protection of systems. This oil also offers excellent rust and corrosion protection even at temperatures as low as -35 °F.

Refer to the label and attached SDS for instructions and precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron

3911 SW 47th AVE

Davie, Florida 33314

Tel: (954) 584 - 4530

Fax: (954) 584 - 4531

www.chemtron.com

