



CT-127

Special Cleaners

WASH & WAX

FEATURES

- Super concentrated formula
- Blend of detergents, surfactants and silicone oil emulsions
- Excellent for car and truck washing
- Does not affect plastics, rubber or paints
- Cleans and shines in one application
- Removes dirt, grease and oils
- Leaves a protective silicone coating that repels water and dirt
- Fast rinsing
- Biodegradable and Environmentally safe

PROPERTIES

Appearance: Thick yellow liquid with hazy appearance and detergent odor

Boiling Point: 212 °F

Specific gravity: 1.02-1.04 gr/cc

Chemical type: Ionic detergents blend 3

Storage stability: Stable for 1 year

% Volatiles: 65-75%


Flammability: Non flammable

Solubility in water: Total

Packaging: Plastic, 5 gal Pails
4 x 1 gal Cases
55 gallon Drum

WASH & WAX is a highly concentrated car wash shampoo that contains cleaning detergents and silicone emulsions, allowing fast rinsing and drying and giving a durable shine to the surface. WASH & WAX leaves a protective coating, that repels water and makes surface more resistant to dirt and stains; also making easier the cleaning job. This concentrate can be used to wash cars, trucks, boats, rail cars, airplanes and most metal surfaces and plastics. To remove heavy soil, dilute 16 oz in a 5 gal bucket with water. For frequent maintenance and light jobs, use 10 oz in 5 gallons water. For high pressure washing, further dilute up to 80 times. For best results pre-wet surface, apply WASH & WAX solution, rub and clean with cloth, sponge or jet; rinse with water and allow to dry. For best shine, buff with dry soft cloth. See label for further directions and refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron
3911 SW 47th AVE
Davie, Florida 33314
Tel: (954) 584 - 4530
Fax: (954) 584 - 4531
www.chemtron.com



- Properties are typical and subject to usual manufacturing tolerances.