

## **ENGINE FUEL CONDITIONER**

## X-10 FUEL CONDITIONER

- Special blend of acid neutralizers, moisture absorption additives and anti wear, corrosion inhibitor
- Removes sludge and varnish
- Cleans injectors and carburetors
- Improves performance
- Reduces downtime and maintenance cost

**Appearance:** Clear red liquid with

**Boiling point:** 190 °F Specific gravity: 0.89 gr/cc Vapor pressure: 200 mmHg Solubility in water: Negligible *Flash point:* 88 °F (Closed Cup)

**Storage stability:** Keep away from open flames, high temperatures and oxidizers.

pH of liquid: 9-10

characteristic odor

Flammability: Flammable liquid Packaging: 1x5 gallon Pail

ChemTron 3911 SW 47th AVE Davie, Florida 33314 Tel: (954) 584 - 4530

> Fax: (954) 584 - 4531 www.chemtron.com

Properties are typical and subject to usual manufacturing tolerances.

X-10 FUEL CONDITIONER is a modern, concentrated fuel conditioner that is specifically engineered to answer the needs of today's high performance engines. It is chemically blended to neutralize fuel acids, as well as to eliminate the damage caused by sulfur, gum, varnish and moisture, which is found in all fuels. The anti wear, corrosion inhibitors and penetrants in X-10 are stable solutions that offer outstanding performance and are safe to use in all types of fuels and engines, including engines equipped with catalytic converters. For gasoline and diesel engines, add 1 gallon of X-10 to 200 gallons of fuel. Use with caution and provide adequate ventilation, as this product is highly flammable and hazardous to ones health. Refer to the label and attached SDS for additional instructions and precautions. The formation contained in this safety sheet is aimed at creating a guide for the lection and use of the product. However, we are not responsible for any use not recommended by ChemTron.