

ENGINE OIL CONDITIONER

X-20 OIL CONDITIONER

- Restores Viscosity Index
- Contains Friction Reducers
- Slows Oxidation
- Increases Oil Pressure
- Reduces Frictional Drag

Appearance: Amber gel with

characteristic odor

Viscosity: 4,000 at 100 °C

Specific gravity: 0.80-0.90 gr/cc

% *VOC by weight:* 1.0 % **Solubility in water:** Slight *Flash point:* 104 °F (40 °C)

Storage stability: Keep away from oxidizing materials and open flames

Flammability: Flammable gel Packaging: 5 gallon Pails 55 gal Drum

> Properties are typical and subject to usual manufacturing tolerances.

X20 Motor Guard Oil Conditioner is a translucent amber, highly viscous, oil conditioner that is fortified with superior oxidation inhibitors to lengthen oil life, increase viscosity, reduce blow by, compression, improve decrease oil consumption and wear internal combustion engines.

Refer to the attached SDS for precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron 3911 SW 47th AVE Davie, Florida 33314 Tel: (954) 584 - 4530

Fax: (954) 584 - 4531 www.chemtron.com

